

1. (Currently Amended) A local network in a vehicle with several subscribers distributed over the vehicle, which form data sources and data sinks and which are connected with one another by a data line to transmit audio, video and control data, such that the audio, video, and control data are transmitted in a format which prescribes a clocked sequence of individual bit groups of the same length, in which certain bit positions are provided respectively for the audio, video, and control data, and the bit positions for the audio or video data respectively are collected together in several connected component bit groups, and the data assigned to these component bit groups are assigned by transmitted control signals to a certain data source or data sink, at least one data source being present for audio and video data and at least one data sink being present for the audio and video data transmitted over the data line, where the at least one data source comprises:

a data source for compressed audio and video digital data, where the bit positions for the audio or video data are collected together in several connected component bit groups, the data source including

a demultiplexer to separate the compressed audio and compressed video data contained in one compressed signal;

a bit stream decoder ~~to that~~ decodes the separated compressed audio data to provide decompressed audio data;

an audio buffer for intermediately storing the ~~separated decompressed~~ audio data and providing buffered decompressed audio data;

a bit rate converter to selectively recode the compressed video data in response to a bit rate control signal to provide recoded video data;

a video buffer for intermediately storing the recoded ~~separated~~ video data;

a bus interface that inserts the ~~decoded~~decompressed audio data and the buffered recoded video data into the corresponding component bit groups, and receives a data sink video characteristic signal and provides a received data sink video characteristics signal;
and

a control unit that is connected to the audio buffer and the video buffer, and which specifies and controls the adjustable intermediate storage time of the audio and video buffers, and in response to the received data sink characteristics signal provides the bit rate control signal.

2. (Previously Presented) The local network of claim 1, where

the data source for compressed audio and video data comprises a data source for other compressed data, where the demultiplexer separates the other compressed data from the compressed audio data and the compressed video data, and where the data source further comprises,

a second bit rate converter for recoding the other compressed data, and

a data buffer for intermediately storing the separated other data, and where the bus interface inserts the decoded audio data, the recoded video data, and the recoded other data into the corresponding component bit groups.

3. (Previously Presented) The local network of claim 1, where at least one of the audio and video buffers is situated before the bus interface.

4. (Previously Presented) The local network of claim 1, where at least one of the audio and video buffers is operationally interposed between the demultiplexer and the bit stream decoder and the bit rate converter associated with the audio and video buffers.

5. (Currently Amended) The local network of claim 2~~12~~, further comprising analytical units associated with the bit stream decoder and the bit rate converters, where the analytical units determine a time relation of the compressed video data with respect to the compressed audio data, and where the analytical units are connected to the control unit to specify the intermediate storage times of the audio, video and other buffers.

6. (Currently Amended) The local network of claim 2~~12~~, where the control unit controls the bit stream decoder and the bit rate converters to synchronize the time relation between the decoded audio data, the recoded video data and the recoded other data.

7. (Previously Presented) The local network of claim 1, where the data line comprises an optical data line.

8. (Currently Amended) The local network of claim 2~~12~~, where the bit rate converter that recodes the compressed video data is connected to the control unit, and where the control unit controls the bit rate converter for the compressed video data to control an amount of data reduction during a bit rate conversion process performed by the bit rate converter in dependence on one of the resolution and the size of a display in the associated data sink for video data.

9. (Previously Presented) The local network of claim 1, where the bit stream decoder decodes the compressed audio data by converting the compressed audio signal into a PCM audio signal.

10. (Previously Presented) The local network of claim 1, where the data source comprises a DVD player.

11. (Previously Presented) The local network of claim 1, where at least one data sink for the data transmitted from the data source via the data line comprises a buffer for the intermediate storage of the received data, where an intermediate storage time of the data sink buffer is adjusted as a function of a control signal transmitted from the data source via the data line.

12. (Cancelled)

13. (Currently Amended) A vehicle-hosted local network comprising:

a subscriber data source that transmits audio digital data and compressed digital video data where the bit positions for the audio or video data are collected together in several connected component bit groups to respective subscriber data sinks on the network, where the subscriber data source includes a demultiplexer that separates compressed audio data and compressed video data contained in one compressed source signal and a pre-processing circuit that processes in parallel the separated audio data and the separated video data to provide decompressed the audio data and the compressed video data that is transmitted to the respective subscriber data sinks on the network, where a control unit receives a data sink video

characteristic signal and provides a received data sink video characteristics signal to a video bit stream converter that processes the compressed video signal in accordance with the data sink video characteristics signal to reduce the bit rate of the compressed video signal and provide a reduced bit rate video signal, where the reduced bit rate video signal and the decompressed audio signal are output to a data sink on the network.

14. (Previously Presented) The vehicle-hosted local network of claim 13, where the subscriber data source comprises:

a device that generates the compressed source signal.

15. (Currently Amended) The vehicle-hosted local network of claim 13, where the pre-processing circuit comprises:

a demultiplexer that separates the compressed audio data and the compressed video data contained in the compressed source signal;

an audio data processing path that decodes the compressed audio data into an uncompressed format and generates decoded audio data in response to control instructions;

a video data processing path that recodes the compressed video data to selectively reduce the quantity of video data in response to the data sink video characteristic signal, and generates the reduced bit rate video signal~~recoded video data in response to control instructions~~; and

a bus interface that combines the decompressed ~~decoded~~ audio data and the reduced bit rate video signal~~recoded video data~~ into component picture groups for parallel transmission over the local network to their respective data sinks, and receives a control signal and provides the data sink video characteristics signal.

16. (Previously Presented) The vehicle-hosted local network of claim 15, where the audio data processing path comprises:

a bit stream decoder for decoding the separated compressed audio data, and for converting the audio data into an uncompressed format; and

an audio buffer for storing the separated audio data for an intermediate time determined by at least one of the control instructions.

17. (Previously Presented) The vehicle-hosted local network of claim 15, where the video data processing path comprises:

a bit rate converter for recoding the compressed video data to reduce the quantity of video data; and

a video buffer for storing the separated video data for a time determined by at least one of the control instructions.

18. (Previously Presented) The vehicle-hosted local network of claim 13, where the subscriber data source comprises:

a device that generates the compressed source signal including compressed audio data and compressed video data; and where the pre-processing circuit separately processes the compressed audio data and the compressed video data to generate uncompressed audio data and a reduced quantity of compressed video data.

19. (Cancelled)

20. (Cancelled)